

This specification describes articles of the material group






PLA – Poly-lactic acid

Material description:

PLA forms through the production of lactic acid from glucose from fermentation. Then a polymerization is added to the resulting lactic acid in the second step. The glucose is obtained here by the grinding and subsequent saccharification from plants which contain starch. Production of PLA in the USA (NatureWorks® Polymer PLA).

PLA can be processed in similar plants as PE: injection moulding, deep-draw, sheet blowing. PLA consists of 100 percent renewable raw materials, has a high stiffness factor, is moisture and grease resistant and has a high gloss. The material is transparent, printable, bio-degradable, food-save but not heat resistant.




Product description

Picture	Description	Article number	Dimensions (mm)
	Straight straws, white	N573	6x250
	Straight straws, green	N574	6x250
	Straight straws, black	N575	6x250
	Straight straws, red	15001	6x250
	Straight straws, white	16397	8x250

PRODUCT-SPECIFICATION__00748/e

DECLARATION OF COMPLIANCE



	Straws cocktail, black	19038	8x150
	Straight straws, green indiv. wrapped	16232	6x230
	Straight straws, black, indiv. wrapped	18918	6x230

Material / composition

PLA (Poly-lactic acid), masterbatch (based on ecoflex)

Storage

Storage temperature: ambient
Relative humidity: dry
Storage conditions: keep away from direct sunlight

Purpose of use

Types of food to be in contact with the material:

- aqueous
- acid
- dairy beverages
- alcoholic

Applications:

- Short-term contact (according to migration test 2h)
- Temperature resistant up to 40°C
- Single-use

PRODUCT-SPECIFICATION__00748/e

DECLARATION OF COMPLIANCE



Declaration of compliance

These articles meet the following regulations and are suitable for direct contact with food :

- Regulation (EC) No 2023/2006** on good manufacturing practice for materials and articles intended to come into contact with food
- Regulation (EC) No 1935/2004** on materials and articles intended to come into contact with food and
- Regulation (EU) No 10/2011** on plastic materials and articles intended to come into contact with food. And subsequent amendments until the date of the test report.
- SR 817.023.21** The Swiss Ordinance on Materials and Articles in Contact with Food

Overall migration

Tested under the following conditions (test report SQTS 2016L22088):

Simulant	Test	Time	Temperature
<input checked="" type="checkbox"/> B: Acetic acid 3 % (v/v)	OML	2h	40°C
<input checked="" type="checkbox"/> D1: Ethanol 50 % (v/v)	OML/SML	2h	40°C

The global migration values are below the limit of 10 mg/dm² and 60 mg/kg.

Specific migration

- No substances with a specific migration limit are observed.

Calculation basis

- Ratio of food contact surface area to volume used to establish the compliance of the material or article: 1 piece / 0.2 kg food.

Heavy metals

No increased heavy metal values (lead, cadmium, chromium, mercury) were detected in the packaging. The sum of the measured elements is below the limit of 100 mg/kg according to the ChemRRV as well as the directive 94/62/EC.

PRODUCT-SPECIFICATION__00748/e DECLARATION OF COMPLIANCE



Production location: Spain

Bio-degradability: The products are completely bio-degradable

Certificates: tested according to DIN EN 13432, certificate no. 7P0616

Customs duty number: 3924.1000

Reclamation

Deliveries, which differ from the listed specifications, will be withdrawn and replaced after review.

Created by: STOL Date: 16.11.2018	Released by: MEI Andreas Meier (Head of Purchasing)		Version: 3
--	--	--	-------------------